



DESCRIPTION:

Universal hose for the woodworking, plastic and chemical industry for transportation of light solids and for air and gas transportation.

PROPERTIES AND APPLICATIONS:

Light and extremely flexible hose with good tensile and abrasion strengths and ultimate elongation. Free of softeners, cadmium free.

MATERIAL:

Wall made of abrasion resistant Polyurethane
- as microbes and hydrolysis resistant version (wall thickness between the spirals ca. 0,6 mm), copper plated spring steel spiral embedded into wall

WORK TEMPERATURE:






-40°C +90°C
(+125°C short term)

RECOMMENDED WORKING PRESSURE:

1/3 of bursting pressure measured at 20°C

OTHER DIAMETERS ON REQUEST

TECHNICAL DATA

				
(mm)	(mm)	(g/m)	(bar)	ambalat in formă comprimată
50	0.6	282	0.27	10 / 15 / 20
60	0.6	337	0.24	10 / 15 / 20
70	0.6	432	0.19	10 / 15 / 20
76	0.6	462	0.19	10 / 15 / 20
80	0.6	492	0.19	10 / 15 / 20
90	0.6	552	0.19	10 / 15 / 20
102	0.6	580	0.14	10 / 15 / 20
110	0.6	625	0.13	10 / 15 / 20
120	0.6	680	0.13	10 / 15 / 20
125	0.6	708	0.11	10 / 15 / 20
130	0.6	736	0.11	10 / 15 / 20
140	0.6	792	0.11	10 / 15 / 20
150	0.6	848	0.09	10 / 15 / 20
160	0.6	903	0.09	10 / 15 / 20
180	0.6	1015	0.08	10 / 15 / 20
200	0.6	1170	0.08	10 / 15 / 20
254	0.6	1315	0.05	10 / 15 / 20
300	0.6	1855	0.03	10 / 15 / 20
350	0.6	2162	0.01	10 / 15 / 20

Specifications are subject to change without notice.



AGRICULTURE INDUSTRY CONSTRUCTION



SCHAUENBURG HOSE TECHNOLOGY GROUP

www.inovaflex.ro info@inovaflex.ro