

### DESCRIPTION:

Universal hose for the woodworking, plastic and chemical industry for transportation of light solids and for air and gas transportation.

### PROPERTIES AND APPLICATIONS:

Medium heavy and flexible hose with good tensile and abrasion strengths and ultimate elongation. Free of softeners, cadmium free

### MATERIAL:

Wall made of abrasion resistant Polyurethane  
- as microbes and hydrolysis resistant version  
(wall thickness between the spirals ca. 0,9 mm),  
copper plated spring steel spiral embedded into wall

### WORK TEMPERATURE:






-40°C +90°C  
(+125°C short term)

### RECOMMENDED WORKING PRESSURE:

1/3 of bursting pressure measured at 20°C

### OTHER DIAMETERS ON REQUEST

### TECHNICAL DATA

				
(mm)	(mm)	(g/m)	(bar)	ambalat in formă comprimată
50	0.9	445	0.33	10 / 15 / 20
60	0.9	531	0.29	10 / 15 / 20
70	0.9	677	0.24	10 / 15 / 20
76	0.9	733	0.24	10 / 15 / 20
80	0.9	771	0.22	10 / 15 / 20
90	0.9	865	0.22	10 / 15 / 20
102	0.9	891	0.22	10 / 15 / 20
110	0.9	960	0.19	10 / 15 / 20
120	0.9	1045	0.19	10 / 15 / 20
125	0.9	1087	0.19	10 / 15 / 20
130	0.9	1130	0.14	10 / 15 / 20
140	0.9	1215	0.14	10 / 15 / 20
150	0.9	1301	0.14	10 / 15 / 20
160	0.9	1386	0.14	10 / 15 / 20
180	0.9	1557	0.11	10 / 15 / 20
200	0.9	1600	0.09	10 / 15 / 20
254	0.9	1797	0.08	10 / 15 / 20
300	0.9	2388	0.06	10 / 15 / 20
350	0.9	2783	0.05	10 / 15 / 20

Specifications are subject to change without notice.



AGRICULTURE INDUSTRY CONSTRUCTION



SCHAUENBURG HOSE TECHNOLOGY GROUP

[www.inovaflex.ro](http://www.inovaflex.ro) [info@inovaflex.ro](mailto:info@inovaflex.ro)